

MOVAX MODULAR SYSTEM - PILING HAMMERS

PILE CAPS

MOVAX piling hammers can be equipped with the following standard type of pile caps (customized pile caps are available upon request):

SHEET PILES / H BEAMS



DH-15, DH-25, DH-35 and DH-45 (S)

for PU and GU sheet piles 600 mm /
H-beam < 500 mm



DH-15, DH-25, DH-35 and DH-45 (M)

for AU sheet piles > 700 mm / H-beams < 700 mm

TUBULAR STEEL PILES, MICROPILES



DH-15 and DH-25

XS Ø 88,9–273 mm



DH-35 and DH-45

XS Ø 88,9–323,9 mm

TUBULAR STEEL PILES

Pile caps are available flat or with either internal or external guidance;

S Ø 273–508 mm

M Ø 406,4–762 mm

(L Ø 762–1220 mm)



PRE-CAST CONCRETE PILES



XS 225 x 225 mm L 350 x 350 mm
S 250 x 250 mm XL 450 x 450 mm
M 300 x 300 mm

Customised, pile caps are available from 180 x 180 mm to 508 x 508 mm.

TIMBER PILES



DH-15, DH-25

Round
XS Ø 90–220
S Ø 220–510

Square
XS 225 x 225 mm
S 250 x 250 mm
M 300 x 300 mm
L 350 x 350 mm



DH-35, DH-45

Round
XS Ø 90–325
S Ø 270–510

Square
XS 225 x 225 mm
S 250 x 250 mm
M 300 x 300 mm
L 350 x 350 mm

NOTE! A single pile cap can handle the given range.

MOVAX MODULAR SYSTEM - PILING HAMMERS

PILE HANDLER

The MOVAX DH piling hammers without rotation device can be equipped with a pile handler for added pile handling capabilities. The pile handler can also be added to existing MOVAX DH piling hammers by simply changing the top cover and adding the pile handler winch and guide.



PILE HANDLER

Technical data

Lifting capacity	kg	2500
Wire rope length	m	36
Total weight (winch, rope, guide)	kg	160